

## **CONTENTS**

### **DATA TRANSMISSION AND PROCESSING**

*A.E. Kuznetsov, P.N. Svetelkin.* OPERATING MATCHING MULTISPECTRAL IMAGES WHILE COLOR SYNTHESIZING

Algorithm of matching multispectral satellite images while color synthesizing is proposed. This algorithm allows defining a priori unknown parameters of reciprocal misalignment on image pyramid in automatic mode. Features of the algorithm practical implementation during receiving color images from "Resurs-DK" spacecraft in operating mode is viewing.....3

*S.N. Kirillov, V.T. Dmitriev.* MODIFICATION OF THE ALGORITHM FIENUPA WHEN RECONSTRUCTION OF SPEECH INFORMATION ON CUT COUNTING OUT THE SIGNAL AND ITS DERIVED

The offered modification iterative algorithm of the reconstruction to speech information on cut counting out the signal and its derived, allowing raise the quality restored speech. It is shown that using given algorithm in codecs speech signal on base band vocoder allows to raise the quality restored speech on 0,3 - 0,4 ballents according to GUEST R 50840-95 .....7

*V.V. Eremeev, N.A. Egoshkin, A.E. Moskvitin.* GEOSTATIONARY SATELLITE IMAGES MATCHING BASED ON USING THE EARTH DISK EDGE POINTS

Technology of automatic evaluation of displacement, rotation and scale distortion of the Earth disk images characteristics is considered. The technology is based on disk edge points definition and analyzing. Precision analyze of the technology is done. The article also has recommendations about its practical use .....10

*K.A. Batenkov.* MODEL OF DISCRETE COMMUNICATION CHANNEL WITH LINEAR-INDEPENDENT SUBCHANNELS

Mathematical model of discrete communication channel is proposed on basis of that requirements to its parameter are determined. The task of basis functions forming is supplied. The claim about method of channel entry and channel exit basis functions systems forming is proved. The task solution by numerical method is found .....17

*A.E. Smirnov.* TRAIN CARRIAGE NUMBER RECOGNIZING USING FUSSY LOGIC METHODS

This article describes a simple method for train carriage number recognizing. The following method intend for use in real-time diagnostic systems. The base of method is fussy equaling of train number and template images .....24

*Y.A. Aldunin.* SYNCHRONIZATION OF TIME IN DISTRIBUTED SYSTEMS, DEPENDING ON CHOSEN CONSISTENCY MODEL

This article is about main methods of time synchronization in distributed systems, about some consistency models. Descriptions for each method of time synchronization according with requirements of each consistency model are given in the end of article .....27

*I.A. Saitov, N.I. Myasin.* OPTIMIZATION OF CHARACTERISTICS OF FIBER-OPTICAL TRANSFER SYSTEMS WITH LINEAR OPTICAL AMPLIFIERS

The new approach to the decision of a problem of increase signaling reliability in fiber-optical transfer system by means of optimization of characteristics of linear fiber-optical amplifiers is offered. Comparison is lead. Sizes of the relation an optical signal/noise at traditional accommodation of linear fiber-optical amplifiers and at their gradient accommodation .....30

### **RADIOTECHNICAL AND MEASURING SYSTEMS**

*B.V. Kostrov, J.V. Konkin.* COMBINATION METHOD RADIOLOCATION PLACE PICTURES

Consider combination method radiolocation picture from radiolocator and model radiolocation picture

place with help invariant moments Hu. Combination execute in order to definition geographical coordinates point of extreme. Adduce results of work algorithm, realizing given method.....35

*P.V. Skoropletov, A.J. Klochkov.* APPLICATION OF THE DIFFERENTIAL FERROPROBE IN SEARCH DEVICES FEELING THE MAGNETIC FIELD

The type of search devices feeling a magnetic field is considered. The analysis of the basic characteristics of the given type of devices is carried out. The most widespread physical principles of construction of magnetometer are considered. The schematic design of the ferroprobe converter executed under the differential circuit is resulted. Practical application of ferroprobe in search devices feeling a magnetic field is proved .....38

*V.G. Lisichkin, E.Y. Naumov.* ANALYSIS OF POWER CONSUMPTION REDUCTION METHODS AT ACTIVE OSCILLATOR MEASUREMENTS

Different power consumption reduction methods of active oscillator measurement devices are considered. The most efficient method being output current decrease of transistors ingoing in active oscillator measurement device is determined. The conclusion about comprehensive approach expediency to energy-saving problem decision at active oscillator measurements is made.....42

*N.A. Matkova.* LASER RECIRCULATION RANGE FINDER WITH GREAT MEASURING RANGE

The main drawbacks of laser recirculation range finder (LRRF) are analyzed. The new approach of expansion of the range of measured distance of LRRF (small distances) with keeping of great accuracy is presented. The basic principles of design and working of the optical scheme of LRRF are developed. The features of the estimation of the optical characteristic of LRRF which worked in the range of small distance (from 0,3 to 50 m ) according to optical scheme are determined.....46

*N.V. Sotnikova, U.V. Petrov.* THE RESEARCH OF ANGLE OF BANK INFLUENCE ON THE DIRECTION-FINDING CHARACTERISTIC OF THE ELLIPTIC FORM ARRAY

In the article the monopulse mode of the airborne radio-locator was examined, the angle of bank influence on the direction-finding characteristic of the elliptic form array was researched. It was shown that when the angle of bank zero offset and steepness of the direction-finding characteristic changed.....49

## COMPUTER SCIENCE AND COMPUTER ENGINEERING

*A.P. Shibarov, N.V. Kravchuk, A.V. Bashev, O.A. Shibarova.* COMPUTER NETWORK CHANNEL SYNCHRONIZATION WHEN TRANSFERRING REAL TIME TRAFFIC

The issue of computer network quality indexed guarantee when transferring real time traffic is considered. The heuristic algorithm of information transfer protocol performances improvement on basis of it's latent parallelism exposure is suggested. The algorithm implementation using GERT (Graphical Evaluation and Review Technique) models is described. Algorithm application allows to decrease the standard deviation of stochastic time between adjacent packets arrivals in 2-3 times in a presence of parallelism in a original protocol.....53

*D.I. Kashirin.* ICF ONTOLOGY FORMALISM FOR KNOWLEDGE REPRESENTATION IN NEW GENERATION OF GLOBAL NETWORK SEMANTIC WEB

In this article the generic ICF-ontology is presented, allowing to describe adequately and to analyze conceptual systems of different domains with considering their concepts from different points of view. The modification of DL logic with ALC grammar is presented, which doesn't break the semantics of logic relative to decidability, which gives an opportunity to use taxonomy embedded to the ICF ontology.....57

*D.L. Zhusov.* MODEL AND ALGORITHM OF SERVICE THE USERS OF THE CORPORATE WEB-SERVER

Are offered model and algorithm of service the users of the corporate web-server. The application of priority rules processing of client searches and introduction the procedure of the registration of self-similarity the going into stream of searches is justified. The rating of efficiency the offered solutions is produced .....64

*S.V. Kroshilina, A.V. Kroshilin.* APPLICATION OF THE IS INDISTINCT-PLURAL APPROACH FOR CONSTRUCTION OF INDISTINCT EXPERT SYSTEMS

The semantic network for the description of the subject domain based on universal algebra in indistinct expert systems is offered. The device of indistinct sets is applied to decision-making. Advantages of the indistinct-plural approach are certain and the expediency of its use in conditions of incompleteness and

an illegibility of a subject domain are proved. The offered model can be adapted under different subject domains ..... 69

*T.A. Dmitrieva.* DEVELOPMENT OF MULTILEVEL MULTITHRESHOLD DECODING DEVICE

The algorithm of multilevel decoding based on multithreshold decoder is offered. The block diagram of the device realizing the given algorithm at a hardware level is developed. The performances of the multilevel multithreshold decoder are obtained. They show an additional power prize in 0,3 dB from application of the offered updating of multithreshold decoder ..... 73

## ELECTRONICS

*D.V. Suvorov, V.A. Korotchenko.* INFLUENCE OF DISCHARGE CIRCUIT INDUCTANCE AND ELECTRODES AREA ON PARAMETERS VOLUME DISCHARGE

By method of numerical modelling influence of spurious discharge circuit inductance and the electrodes area on characteristics of the volume discharge are investigated for conditions of nitrogen laser. It is established, that with decreasing spurious discharge circuit inductance from 200 up to 2 nanohenry efficiency of the laser substantially (a few times) increases, and at the further decreasing of inductance it increases only for 20 %. With increase electrodes area up to 5 cm<sup>2</sup> reaching values of inversion and efficiency of the laser increase approximately twice, and further increase poorly ..... 79

*D.V. Kirjushin.* ASYMPTOTICS OF DRIVING OF IONS IN LINEAR RF FIELDS WITH A QUADRATIC POTENTIAL DISTRIBUTION AT PRESENCE OF BUFFER GAS

With use of representations of the theory of acceptance the analytical technique is developed for an estimation of effect of collisions of ions and molecules on amplitude of driving of ions. Expressions for the limiting values of coordinates of charged particles are gained. Analytical calculations prove to be true outcomes of computer model operation ..... 82

*S.P. Vikhrov, N.V. Vishnyakov, V.G. Mishustin, K.O. Anoshkin.* THE CARRIER TRANSPORT THROUGH BARRIER BETWEEN METAL AND DISORDERED SEMICONDUCTOR: PECULIARITY OF FORWARD AND REVERSE CURRENT-VOLTAGE CHARACTERISTICS CALCULATIONS

The calculation method of forward and reverse current-voltage characteristics of the contact between metal and disordered semiconductor is suggested. It is based on the classic diffusion theory for crystalline semiconductors with account of disordered semiconductor materials energy-band structure and electro-physical properties peculiarities. The analytical expression for reverse current-voltage characteristic is deduced. It takes into account the decrease of effective barrier height because of carrier tunneling through the thin barrier layer. The description way of carrier transport through the barrier between metal and disordered semiconductor as opposite barriers system is suggested ..... 86

*E.V. Mamontov, I.V. Philippov, A.A. Dyagilev.* PULSE ION SOURCE FOR RADIOFREQUENCY TIME-OF-FLIGHT MASS SPECTROMETER

Simple pulse ion source for radiofrequency time-of-flight mass spectrometer is described. Two hyperbolic electrodes of the ion source generate electric field with quadratic potential distribution which enables effective time focusing of ions. The results of computer simulation are presented and discussed ..... 88

*B.A. Stepanov, M.M. Afanasova.* COMPARATIVE ANALYSIS OF THE PARAMETERS AND BEHAVIOUR OF ELECTRON GAS IN HETEROSTRUCTURES INAS/ALSB AND AL<sub>x</sub>GA<sub>1-x</sub>AS

In the presents article the experiments on degenerated 2D electrons in heterostructures InAs/AlSb и Al<sub>x</sub>Ga<sub>1-x</sub>As at two  $E_m$  and  $E_p$  dimensional quantization subbands are discussed. The significant difference of two dimensional electron systems is due to heterostructure layer architecture and, therefore, energy spectrum structure and electronic density spatial distribution. These parameters predefine dimensional quantization subbands population dynamics and influence the intra- and intersubband e-e relaxation character which arises in the phenomena of oscillation amplitude-frequency modulation and Landau quantization dampin ..... 91

## BRIEF REPORTS

*O.V. Palchik.* FILTRATION OF THE SINGLE IMPULSE TOGETHER WITH THE POSITION

## ESTIMATION OF ITS EXTREMUM

In the article the question of an estimation of time position of a single impulse in structure of a signal of the limited extent is considered. This question is actual in a radio engineering. Procedure of a low-frequency filtration of a signal is analyzed. Procedure of an estimation of position of the impulse, based on

differentiating property of filters with not even pulse characteristic is offered joint with a low-frequency filtration ..... 99

*A.S. Stukalova.* THE USING OF WAVELET-TRANSFORMATIONS FOR GEOPHYSICAL SIGNALS INTERPRETATION AND MEASURING-IN SPEED OF ACOUSTIC WAVE PROPAGATION

The article reviews potentialities of the detailed geophysical signal analysis and dependent on frequency speed of acoustic wave propagation measuring-in. The analysis properties local signal algorithm and speed of acoustic wave propagation on the base of discrete wavelet-transformations measuring-in are offered. For increase self-descriptiveness and increase of effectiveness processing and interpretation geophysical signal use of wavelet-transformations seismic signal the advisability is shown..... 103

*V.V. Tarasov.* TO THE PROBLEM OF THE POSSIBILITY OF BOOLEAN FUNCTIONS OVER THE BASIS OF STOCHASTIC

Boolean functions on the foundation of extensions of Post-classes containing constants conditions of the possibility of Boolean functions by means of formulas over the basis of stochastic Boolean functions are researched..... 106

*A.S. Kudryavtsev.* ADAPTATION OF THE RUSSIAN COMPANIES TO REQUESTS OF ISO 9001:2000

Many heads of the domestic companies for increase of competitiveness and quality of production have gone on a way of introduction of systems of quality management under standard ISO 9001:2000. However the majority of these projects either has ended with failure, or was reduced only to reception of the certificate of conformity and in a result has not resulted in expected results. In the message features of reduction Cof systems of quality management of the enterprise in conformity with requirements of standard ISO 9001:2000 are considered, the program on reduction of systems of quality management conformity with requirements ISO 9001:2000. is developed are in detail considered stages « Positioning of activity of the company» and «the Analysis and correction of systems of quality management». Use of the similar approach is for the Russian enterprises the necessary tool in the decision of problems in the field of maintenance of quality of production..... 109

*N.M. Turusikova.* INVESTIGATION OF MATHEMATICAL MODEL CONTROL OF INVESTMENT PORTFOLIO IN CONTINUOUS TIME

This article is devoted to the problem of investment portfolio control. Investment portfolio is supposed to contain financial holdings. In continuous time investment portfolio mathematical model is described by the system of differential equation. The problem of investment portfolio control is formulated as achievement of a certain level of yield during some period of time. They suggest an approach to define proper controlling measures and deduce yield equation under a found form of control..... 109

*A.S. Slesarev.* OPTIMIZATION OF SECOND ORDER PLL CIRCUIT LOOP FILTER OF SATELLITE COMMAND-PROGRAMM RADIO LINKS CLOCK SYSTEM

The basis of optimality test of satellite command-program radio links second order PLL circuit loop filter in the presence of ramp dopler shift is presented. Optimization of loop filter coefficients for different signal-to-noise ratios is carried out. It is shown that the loop filter optimized for signal-to-noise ratio of -25 dB provides the best stability to signal-to-noise ratio change in the range from -30 dB to -10 dB ..... 115

*L.V. Gimpelson.* THE MODEL “QUALITY OF ORGANIZATION” AND THE METHOD FOR ESTIMATION OF QUALITY OF ORGANIZATION FOR RISE OF EFFECTIVENESS PRODUCTION OF METAL TREATMENT

The notion “quality of organization” is interroduced. The method for estimation of quality of organization is offered. Example this method on a process of metal treatment is considered..... 118

THE ITEMS OF INFORMATION ON THE AUTHORS ..... 122