

CONTENTS

DATA TRANSMISSION AND PROCESSING

- B.A. Alpatov, P.V. Babayan, V.V. Strotov.* ANALYZE OF PRECISION CHARACTERISTICS OF BACKGROUND IMAGE TRACKING METHODS FOR ON-BOARD VIDEO COMPUTING SYSTEM
The problem of shift and rotation of background image parameters in video sequence estimating is observed. Two algorithms for solving proposed problem are described. Results of comparison experiments for this algorithms are given. Recommendations for using this methods in board video computing system, based of researching, are stated3
- V.A. Goncharov, V.N. Przegorlinskiy.* SECURE OS AND NETWORK INTRUSION DETECTIONS SYSTEMS NETWORK ATTACKS COUNTERACTION ABILITIES ANALYSIS
Secure OS access control implementation was examined. Attack and attack phases were defined. Attack counteraction by Intrusion Detection Systems was examined. Attack phases implementation classification was defined. Comparison of secure OS and Local and Network Intrusion Detections Systems attack counteraction was done 10
- S.S. Mamonov.* THE MODES OF SYNCHRONIZATION OF SYSTEM OF SECOND ORDER FREQUENCY PHASE-FREQUENCY AUTOMATIC CONTROL
The paper deals with the system of second order phase-frequency synchronization. There are values of parameters of the system for modes of synchronization. The conditions of existence of three second degree limit cycles are got. The nature of their stability is being realized. The attraction region for the system with sinusoidal non-linearity has been created in case of limit cycles of the second degree exist 14
- V.V. Tarasov.* ABOUT THE COMPLETENESS OF FINITE SYSTEMS OF STOCHASTIC BOOLEAN FUNCTIONS
Necessary and sufficient conditions of completeness of stochastic systems BOOLEAN functions are being proved..... 19
- S.V. Panov, D.M. Karabash, A.T. Kizimov, D.R. Berezin, L.E. Frolova.* INERTIAL SENSORS INTEGRATION WITH GPS INSTALLED IN UNMANNED AERIAL VEHICLE (UAV)
Model for device of optimal integrated processing of the inertial sensor and GPS signals is built on basis of estimation error variance minimum criterion by the example of the estimation unit for UAV vertical channel parameters. The following estimations are obtained: flight altitude with error of not more than 25 m, UAV vertical speed with error of not more than 0,2 m/s, barometric altimeter systematic inaccuracy with error of not more than 23 m.....25
- Pham Xuan Nghia.* ANALYSIS OF USING THE ALGORITHM MC-ELIECE SIGNATURE SCHEME
Offered using algorithm public key Mc-Eliece for electronic digital signature. It Is shown that in this case use the algorithm Mc-Eliece raises the secretiveness of information in 10^{50} times. Using the parallel codes in algorithm Mc-Eliece, except extensions space keys, allows to raise vastly cryptography resistance information, as well as in two times digital signature in compare with source algorithm on base of the simple linear codes30

RADIOTECHNICAL AND MEASURING SYSTEMS

V.V. Ezerski. INFLUENCE of NOISE ON ACCURACY of RANGE SENSING by RANGE FINDER WITH ADAPTIVE FREQUENCY MODULATION

It is considered inaccuracy of measurement of distance by range finder with adaptive frequency modulation, caused by influence of noise on process of adapting the parameters to modulations. Happen to the expressions for relative dispersion of inaccuracy of measurement of distance under two possible ways of estimation an difference of frequency. It is executed quantitative estimations inaccuracy of measurement and brought results of computer modeling35

S.N. Kirillov, A.S. Slesarev. THE ALGORITHM OF INFORMATION TRANSMISSION SATELLITE SYSTEMS PHASE-SHIFT KEYED COMPOUND SIGNALS DETECTION UNDER LOW SIGNAL-TO-NOISE RATIO

Periodic manipulating pseudorandom sequence phase-shift keyed compound signals detection algorithm, which uses dual-threshold processing of cross-correlation function of received and reference signals as well as cross-correlation function accumulation at several pseudorandom sequence periods, is developed. The developed algorithm requires 2..5 times less capacity of additional memory for accumulated cross-correlation function storing with small (0,5..1%) probability of detection decrease41

A.D. Tokar. COMPARATIVE ANALYSIS OF DYNAMIC ERRORS FOR PROPORTIONAL POINTING METHOD AND MODIFIED ALGORITHM OF POINTING FOR AIR TARGET

Brought comparative analysis of dynamic errors for proportional pointing method and modified algorithm of pointing for air target. Showed, that modified method of pointing for distant and not maneuvering objects has same quality performances, that traditional proportional pointing method. However with short distant beginning of self-direction, modified method has less value of current missing44

V.M. Davidotchkina. INFLUENCE OF THE “VIRTUAL OBSTACLES” ON THE ESTIMATION ERROR OF THE FREQUENCY OF THE BEAT SIGNAL PRODUCED BY THE FREQUENCY-MODULATED CONTINUOUS WAVE LEVEL GAUGE

We consider the estimation error of the frequency of the beat signal produced by the frequency-modulated continuous wave level gauge, caused by the influence of the combinational obstacles and the accompanying waves, reflected from the imperfections of the antenna and the feeding waveguide. We determine the performance requirements for the antenna, waveguide and the transceiver to minimize the aforementioned component of the measurement error. We also propose a method of reducing this error by setting the parameters of the windowing function during the processing of the beat signal47

O.A. Astafurova. RADIATION AERIALS CHARACTERISTICS MEASUREMENTS ON THE BASIS OF THE EDGE-DIELECTRIC TRANSMISSION LINE

The design of the aerial on the basis of edge-dielectric transmission line as well as experimental characteristics of its radiation and its dependence on the geometrical sizes of directing structure are submitted. The research on frequency characteristics of aeriels on the basis of edge-dielectric line is carried out54

S.A. Bahurin, A.A. Cyplakov. ALGORITHM OF THE SYNTHESSES AND PROCESSING THE CODE SEQUENCES WITH MINIMUM LEVEL LATERAL PETAL AUTOCORRELATION FUNCTION ON BASE WAVELET-PACKET DECOMPOSITION

Algorithm of the syntheses and processing the code sequences of phase-shift keyed signals on base single-level wavelet-packet decomposition is offered. It is shown that algorithm of the processing provides the advantage in noise-immunity of the order 2...6 dB at influence of the

pulsed hindrance and 0,5...6 dB at influence of the structured hindrance in contrast with algorithm of the processing M- sequences and D-codes Velti 58

A. N. Varnavsky, O.V. Melnik, A.A. Miheev. DEFINITION OF RR-INTERVAL DURATION AVERAGE VALUE IN THE REAL-TIME MODE

In article the new approach to definition of RR-interval duration average value, based on the analysis of electrocardiosignal energy change in a strobe pulse is offered. The opportunity of present approach realization as the device on discrete elements is shown..... 61

E.V. Gusev, A.N. Shesterkin. ANALYTICAL ESTIMATION OF DENSITIES OF PROBABILITIES DISTRIBUTION OF THE LIGHTING LAG TIME OF PARALLEL EXCITED GAS DISCHARGE DISPLAY REFLECTION ELEMENTS

We have obtained the analytical expressions, which allow to simplify the estimation of limit values of lighting reliability of parallel excited elements 65

SYSTEMS OF AUTOMATED DESIGNING

A.P. Shibarov, N.V. Kravchuck. USING OF GERT MODELS IN COMPUTER NETS OPTIMIZATION

In this article the methods for computer nets local parametrical optimization are examined. In GERT net the branches set is picket out by functional, informational or structural characteristics. GERT nets consisting of partial nets with additive conditions execution its output stochastic values are described. The method of parametrical optimization with using of branch execution time average value and calculation of its final result influence degree is offered 69

A.I. Ignatiev. ASSESSMENT OF CRITERIA OPTIMIZING MOTO TRANSPORTATION FOR SPECIALIZED SMALL AND MIDDLE FIRMS

In the article we analyse the scheme determining criteria for assessment of using motor transfer companies. We use several criteria to improve its work and assess its efficiency. We use such indices is – the length of the way, v — speed, λ — rate (quantity of objects per unit time). We consider the role of the following factors in the procedure: the seasonality and the place of delivery (C), the place of delivery and the specificity of the transport (M); the specificity of the transport and delivery dates (B) 75

A.I. Baranchikov, P.A. Baranchikov. ORGANIZATION OF RECORD – SPECIFIC ACCESS TO DATABASE TABLES

The problem of record-specific database table access organization is covered. The five realization variants of such organization are suggested. The relational algebra apparatus was used during the investigation. The following criteris was copared: system complicity, software and hardware demand. As a result of investigation, 3 methods of access organization was selected with usage area instructions, depending on developing information systems specific 78

V.I. Koshelev, Nguyen Duc Tuan. TRAINING MULTILAYER NEURAL NETWORKS WITH BACK PROPAGATION ALGORITHM

The benchmark analysis different training algorithm for multilayer neural networks in the problem recognition air objects by range patterns is executed. It is shown that the conjugate gradient algorithm is the best choice for this problem in the most cases. The best training velocity value for the gradient decent algorithm is defined ($\mu \leq 0.1$) 81

A.P. Kazantsev, A.A. Senin, O.V. Pikulenko. DESIGN AND IMPLEMENTATION OF MOBILE TELEMEDICINE NETWORK FOR REMOTE ELECTROCARDIOGRAPHY

Architecture of mobile remote computerized electrocardiography system is proposed. The system

designed as a corporate IP network of portable microcomputer based wirelessly connectable recorders and service analyzers. Uniform computerized systems of two types were developed and implemented – Telecardiac Emergency System and Mobile Remote Cardiovascular Diagnostic System.....85

M.A. Kudashev. ABOUT TWO ALGORYTHMS OF ANALYSIS THAT PROVIDE CERTAIN CHARACTERISTICS OF COMMUNICATION NETWORK
We consider one of the most important problem of nowadays, that of station repeater location. We have formulated the task and have indicated possible ways of solution.....90

N.Yu. Chlebnikov. A METHOD OF QUALITY EVALUATION OF INFORMATION-MANAGEMENT SYSTEM OF CHEMIKAL WEAPON STORAGE AND DESTRUCTION TECHNICAL SECURITY
Characteristics of an information-management system of chemical weapon storage and destruction technical security are considered and a criterion for complex evaluation of the system quality is suggested94

ELECTRONICS

S.P. Borisovskiy, M.Y. Kernosov, V.A. Stepanov, E.G. Chulyaeva. RESEARCH OF PROPERTIES OF LASER RADIATION OF THE UNFREQUENTED LASER OF THE RAISED CAPACITY
Results of research of properties of laser radiation of the unifrequent laser of the raised capacity are resulted. The major factors influencing for coherence length of the unifrequent laser of raised capacity are shown and calculated. Influence of thermal expansion of the quartz standard the Fabri-Pero on stability of capacity of laser radiation and for the coherence length is shown. It is illustrated, that small temporal coherence of the laser radiation is caused by temperature fluctuations of length of the quartz standard the Fabri-Pero99

V.A.Korotchenko, D.V.Suvorov. THE SELF-CONSISTENT MODEL OF FORMATION VOLUME DISCHARGE I. A PHYSICOMATHEMATICAL BASIS OF MODEL
The model of the gas-discharge processes including self-consistent calculation of redistribution of potential in an discharge gap together with electrodynamic external circuit and calculation of photoissue electrons from the cathode separately for each spectral line of radiation discharge is presented. The features of model providing high stability and effectivity calculation are described. Results of modelling for the nitrogen laser are presented.....103

BRIEF REPORTS

V.T. Dmitriev, D.A. Kulyasova. DEVELOPMENT OF THE DESIGNING METHODS OF THE IP-TELEPHONY NETWORKS
The united methods of the designing the networks IP-telephony is designed. Given methods can be used when designing the real networks or be used under degree and курсовом designing student of the direction "Telecommunications"108

I.V. Chernov. FEATURES OF CALCULATION OF STABILITY DIGITAL RADIO RELAY LINES
The method of specification of a design procedure of stability of work of intervals digital RRL in conditions interferential fading is considered. Use medians factor the easing, the formula received experimentally for an estimation of statistics such fading is offered. Advantage of use of the given method is shown at designing high-mountainous lines.....111

I.V. Kostkin. ALGORITHM WAVELET-COMPRESSIONS OF THE STATIC DIGITAL IMAGE

The Offered algorithm wavelet-compressions still digital image. In base of the algorithm as one should execution wavelet-transformations with use of the new base on each step of the decomposition. It is received vector base class Dobeshi, providing maximum compression 8-bit monochrome image. The organized comparison of the offered algorithm with standard JPEG and JPEG2000	114
<i>Bui Le Nam.</i> THE ENERGY LOSS IN LOCATION OF THE ULTRA-WIDEBAND SIGNAL The comparison of the efficient losses in the location when using ultra-wideband signals. It is shown that possible use the type ultra-wideband signal, allowing reduce the efficient energy losses in the location of the reflex signal from object, under fixed angular sector of probing signal of the antenna array.....	117
<i>A.S. Kudryavtsev.</i> INTRODUCTION OF SYSTEM OF QUALITY ON THE SMALL ENTERPRISE Certification of control systems by quality on conformity of International Organization for Standardization 9000 now receives wide evolution in Russia. All increasing number of the enterprises chooses certification as an effective method of increase of competitiveness The sequence of development cycles and documenting of system of quality, and also feature and arising problems are considered at its introduction.....	120
THE ITEMS OF INFORMATION ON THE AUTHORS	124